



SNR Bearing Argentina



160 mm x 200 mm x 20 mm NSK 6832DDU
deep groove ball bearings

Bearing No. 6832DDU

6832DDU Bearing 2D drawings and 3D CAD models

| | |
|-------------------------------|--------------------------|
| Size | 160x200x20 mm |
| Bore Diameter | 160 mm |
| Outer Diameter | 200 mm |
| Width | 20 mm |
| d | 160 mm |
| D | 200 mm |
| B | 20 mm |
| C | 20 mm |
| r min. | 1,1 mm |
| da min. | 166,5 mm |
| da max | 170,5 mm |
| Da max. | 193,5 mm |
| ra max. | 1 mm |
| Weight | 1,23 Kg |
| Basic dynamic load rating (C) | 48,5 kN |
| Basic static load rating (C0) | 61 kN |
| (Grease) Lubrication Speed | 1 700 r/min |
| Category | Single Row Ball Bearings |
| Inventory | 0.0 |
| Manufacturer Name | NSK |
| Minimum Buy Quantity | N/A |
| Weight / US pound | 1.23 |
| Product Group | B00308 |
| Enclosure | 2 Seals |
| Precision Class | ABEC 1 ISO P0 |



SNR Bearing Argentina

| | |
|---------------------------------|--|
| Maximum Capacity / Filling Slot | No |
| Rolling Element | Ball Bearing |
| Snap Ring | No |
| Internal Special Features | No |
| Cage Material | Steel |
| Enclosure Type | Contact Seal |
| Internal Clearance | C0-Medium |
| Inch - Metric | Metric |
| Long Description | 160MM Bore; 200MM Outside Diameter; 20MM Outer Race Width; 2 Seals; Ball Bearing; ABEC 1 ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features; C0-Medium Internal Clearance; Steel Cage |
| Other Features | Deep Groove Rubber Seal |
| Category | Single Row Ball Bearing |
| UNSPSC | 31171504 |
| Harmonized Tariff Code | 8482.10.50.68 |
| Noun | Bearing |
| Keyword String | Ball |
| Manufacturer URL | http://www.nskamericas.com |
| Manufacturer Item Number | 6832DDU |
| Weight / LBS | 1.23 |
| Inner Race Width | 0 Inch 0 Millimeter |
| Outside Diameter | 7.874 Inch 200 Millimeter |
| Bore | 6.299 Inch 160 Millimeter |
| Outer Race Width | 0.787 Inch 20 Millimeter |
| SRI | 6.16 |
| hidYobi | 6832DDU |
| LangID | 1 |
| | |



SNR Bearing Argentina

| | |
|------------|-------------|
| D_ | 200 |
| SREX | 0.025 |
| B_ | 20 |
| da min | 166.5 |
| hidTable | ecat_NSRDGB |
| SRE | 6.16 |
| mass | 1.23 |
| GRS rpm | 1700 |
| ra | 1 |
| SRIX | 0.025 |
| D_a | 193.5 |
| SRIN | -0.025 |
| C0 | 61 |
| fo | 17.2 |
| SREN | -0.025 |
| DE_ | 191.906 |
| Prod_Type3 | DGBB_SR_DD |
| DA_ | 11.906 |
| bomp | 0 |
| Z_ | 25 |
| yobi | 6832DDU |
| C_conv | 48500 |
| ALPHA_ | 0 |
| SDM_ | 180 |
| r | 1.1 |
| KBRG | 6161 |
| SBRG | 18 |
| DI_ | 168.094 |